

View Online at <https://aerobasegroup.com/nsn/5315-01-478-5566>

Handle Length:

Between 1.720 inches and 1.820 inches

Shank Diameter:

0.311 inches

Detent Quantity:

4

End Application:

Helicopter, attack

Grip Length:

5.183 inches

Actuation Type:

Push

Shear Strength:

14400 double pounds per square inch

Shoulder To Head End Distance:

Between 0.890 inches and 1.300 inches

Detent To Tapered End Distance:

Between 0.370 inches and 0.380 inches

Product Name:

Single acting, positive locking quick release pin

Special Features:

Heat treat shank and spindle rc 40 min per mil-h-6875; ball hardness 58-62; corrosion resistant steel parts are passivated per qq-p-35 and alluminum alloy parts are anodized mil-a-8625, handle to be dyed dark gray or black and button to be dyed blue; lanyard is 12 inches long and cable size is 1/16 diameter cres, vinyl coated, color green per mil-i-631, rated full strength, 480 lbs, swaging sleeve, nicopress 28 ic or equiv

Material:

Steel comp 630 spring or steel comp 302 spring

Material Specification:

Ams5678 assn standard single material response spring or astm-a-313 assn standard single material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec