

View Online at <https://aerobasegroup.com/nsn/5315-01-478-5566>

**Handle Length:**

Between 1.720 inches and 1.820 inches

**Shank Diameter:**

0.311 inches

**Detent Quantity:**

4

**End Application:**

Helicopter, attack

**Grip Length:**

5.183 inches

**Actuation Type:**

Push

**Shear Strength:**

14400 double pounds per square inch

**Shoulder To Head End Distance:**

Between 0.890 inches and 1.300 inches

**Detent To Tapered End Distance:**

Between 0.370 inches and 0.380 inches

**Product Name:**

Single acting, positive locking quick release pin

**Special Features:**

Heat treat shank and spindle rc 40 min per mil-h-6875; ball hardness 58-62; corrosion resistant steel parts are passivated per qq-p-35 and alluminum alloy parts are anodized mil-a-8625, handle to be dyed dark gray or black and button to be dyed blue; lanyard is 12 inches long and cable size is 1/16 diameter cres, vinyl coated, color green per mil-i-631, rated full strength, 480 lbs, swaging sleeve, nicopress 28 ic or equiv

**Material:**

Steel comp 630 spring or steel comp 302 spring

**Material Specification:**

Ams5678 assn standard single material response spring or astm-a-313 assn standard single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

T handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec