

View Online at <https://aerobasegroup.com/nsn/5315-01-480-0830>

First End Style:

Chamfered

Second End Style:

Chamfered

Thread Class:

3a

Thread Length:

0.405 inches

Shank Length:

1.468 inches

Shoulder Diameter:

0.438 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Overall Length:

2.218 inches

End Application:

Signal process

First End Taper Length:

0.030 inches

Second End Taper Length:

0.250 inches

Thready Qty Per Inch (tpi):

28

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

Second Shank Diameter:

Between 0.249 inches and 0.250 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Second End Tip Radius:

Between 0.060 inches and 0.090 inches

Second Shank Length:

0.625 inches

Product Name:

Pin, index

Special Features:

Shoulder diameter 0.125 in; grip 1.063 in; width between the flats 0.438

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0