

View Online at <https://aerobasegroup.com/nsn/5315-01-480-0830>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Length:**

0.405 inches

**Shank Length:**

1.468 inches

**Shoulder Diameter:**

0.438 inches

**Shank Diameter:**

Between 0.249 inches and 0.250 inches

**Overall Length:**

2.218 inches

**End Application:**

Signal process

**First End Taper Length:**

0.030 inches

**Second End Taper Length:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.250 inches

**Second Shank Diameter:**

Between 0.249 inches and 0.250 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Second End Tip Radius:**

Between 0.060 inches and 0.090 inches

**Second Shank Length:**

0.625 inches

**Product Name:**

Pin, index

**Special Features:**

Shoulder diameter 0.125 in; grip 1.063 in; width between the flats 0.438

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0