NSN 5315-01-482-3587

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-482-3587

view Online at https://aerobasegroup.com/nsn/3010-01-402-330/
First End Style:
Chamfered
Thread Class:
2b
Thread Direction:
Right-hand
Thread Length:
0.940 inches
Shank Length:
1.750 inches
Shoulder Diameter:
Between 0.500 inches and 0.502 inches
Shank Diameter:
0.375 inches
Overall Length:
3.500 inches
End Application:
Cargo carrier; bradley
First End Taper Length:
0.060 inches
Thready Qty Per Inch (tpi):
16
Second End Relationship With First End:
Identical
Thread Size:
0.375 inches
First End Location:
Threaded end
First End Taper Angle:
Between 43.0 degrees and 47.0 degrees
Material:
Steel comp 4140h or steel comp 4145h or steel comp 4147h or steel comp 8640 or steel comp 8740
Material Specification:
Astm a304 assn standard 1st material response or astm a304 assn standard 2nd material response or astm a304 assn standard 3rd
material response or astm a322 assn standard 4th material response or astm a322 assn standard 5th material response or ast a331 assn
standard 4th material response or astm a331 assn standard 5th material response
Surface Treatment:
Zinc
Surface Treatment Specification:
Astm b633, type ii assn standard single treatment response
Style Designator:
Shoulder

Unc

Thread Series Designator:

NSN 5315-01-482-3587

Headless Shoulder Pin - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0