## NSN 5315-01-482-7547

Headless Shoulder Pin - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5315-01-482-7547



First End Style: Square **Second End Style:** Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.405 inches **Shank Length:** 0.593 inches **Shoulder Diameter:** Between 0.430 inches and 0.439 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Overall Length:** 1.343 inches **End Application:** Pallet assembly; f/a-18 hornet **Second End Taper Length:** Between 0.248 inches and 0.252 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches **Second Shank Diameter:** Between 0.2490 inches and 0.2495 inches First End Location: Threaded end **Second End Tip Radius:** Between 0.060 inches and 0.090 inches **Second End Taper Angle:** 45.0 degrees **Second Shank Length:** 0.625 inches Material:

Material Specification:

Steel comp xm-13

Ams 5629 assn standard single material response

## NSN 5315-01-482-7547

Headless Shoulder Pin - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A212a0