NSN 5315-01-483-0363

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-483-0363 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.450 inches **Shank Length:** 0.655 inches **Shoulder Diameter:** Between 0.430 inches and 0.439 inches **Shank Diameter:** Between 0.249 inches and 0.250 inches **Overall Length:** 1.275 inches **End Application:** Aircraft, hornet, f/a, 18 First End Taper Length: 0.030 inches **Second End Taper Length:** 0.120 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees **Second End Tip Radius:** Between 0.060 inches and 0.090 inches **Second Shank Length:** 0.495 inches **Product Name:** Pin, index

Material:
Steel comp 302 or steel comp 303 or steel comp 304

NSN 5315-01-483-0363

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Ams-qq-s-663 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams-qq-p-35 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A212a0