NSN 5315-01-483-3580

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-483-3580

Head Diameter:

Between 0.410 inches and 0.590 inches

Shank Diameter:

Between 0.3095 inches and 0.3110 inches

Ring Handle Diameter:

1.060 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

0.900 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c

Shear Strength:

14400 double pounds per square inch

Shoulder To Head End Distance:

0.830 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.330 inches

Material:

Stainless steel

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Ring handle

Test Data Document:

81349-mil-p-23460 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms17987 government standard

Shelf Life:

N/a

- Unit Of Measure:
- ---
- Demilitarization:
- No

NSN 5315-01-483-3580

Quick Release Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard):

Mil-p-23460 spec.

