## NSN 5315-01-483-3580

Quick Release Pin - Page 1 of 2

Between 0.410 inches and 0.590 inches

Between 0.3095 inches and 0.3110 inches

**Head Diameter:** 

**Shank Diameter:** 

1.060 inches

Detent Quantity:

2

Ring Handle Diameter:



View Online at https://aerobasegroup.com/nsn/5315-01-483-3580

Actuation Method:
Push button
Grip Length:
0.900 inches
Actuation Type:
Push
Hardness Rating:
40.0 rockwell c
Shear Strength:
14400 double pounds per square inch
Shoulder To Head End Distance:
0.830 inches
Pin Attachment Type:
Link or ring
Detent To Tapered End Distance:
0.330 inches
Material:
Stainless steel
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Ring handle
Test Data Document:
81349-mil-p-23460 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms17987 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

## NSN 5315-01-483-3580

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-p-23460 spec.