# NSN 5315-01-484-1235

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-484-1235

#### Shank Diameter:

Between 0.4970 inches and 0.4995 inches

# **Detent Quantity:**

2

# Actuation Method:

Push button

#### **End Application:**

Adapter, grnd; f/a-18e/f hornet aircraft

#### Grip Length:

Between 1.200 inches and 1.220 inches

#### Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shear Strength:

36900 double pound

#### Shoulder To Head End Distance:

1.820 inches

#### Pin Center To Handle End Distance:

2.000 inches

#### Pin Attachment Type:

Hook or ring

# **Detent To Tapered End Distance:**

0.530 inches

Material:

Steel comp 632 spindle or steel comp 630 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### Style Designator:

L handle

#### **Specification Data:**

80208-nas1338 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# **NSN 5315-01-484-1235** Quick Release Pin - Page 2 of 2

Fiig: A212a0

