# NSN 5315-01-484-1259

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-484-1259

#### Shank Diameter:

Between 0.621 inches and 0.624 inches

# **Button Handle Diameter:**

1.600 inches

# **Detent Quantity:**

2

# Actuation Method:

Push button

#### **End Application:**

Adapter, grnd; f/a-18e/f hornet aircraft

#### Grip Length:

Between 2.100 inches and 2.120 inches

#### Actuation Type:

Push

#### Hardness Rating:

#### 40.0 rockwell c spindle

Shear Strength:

# 57500 double pound

#### Shoulder To Head End Distance:

1.820 inches

# Pin Attachment Type:

Hook or ring

# Detent To Tapered End Distance:

0.650 inches

# Material:

Steel comp 632 spindle or steel comp 630 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### **Style Designator:**

Button

#### **Specification Data:**

80208-nas1340 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# **NSN 5315-01-484-1259** Quick Release Pin - Page 2 of 2

Fiig: A212a0

