NSN 5315-01-484-1448

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-484-1448 First End Style: Chamfered Second End Style: Slotted **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.386 inches First Step Diameter: 0.500 inches First Step Length: 0.750 inches **Second Step Diameter:** 0.437 inches **Second Step Length:** 0.440 inches **Third Step Diameter:** 0.375 inches Third Step Length: 0.520 inches **End Application:** Adapter, grnd; f/a-18e/f hornet aircraft **Second End Slot Width:** 0.090 inches First End Taper Length: 0.046 inches **Second End Slot Depth:** 0.090 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.375 inches **First End Location:** Threaded end First End Taper Angle: 45.0 degrees **Second End Outer Radius:**

0.120 inches

NSN 5315-01-484-1448

Headless Shoulder Pin - Page 2 of 2



| Material: |
|--|
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758, cond d military specification single material response |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |

Mil-std (military Standard):

Mil-s-6758 spec.