NSN 5315-01-485-6753

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-485-6753 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** 24 **Thread Direction:** Right-hand Thread Length: 0.430 inches **Shank Length:** Between 0.677 inches and 0.697 inches **Shoulder Diameter:** 1.250 inches **Shank Diameter:** Between 0.310 inches and 0.312 inches **Overall Length:** Between 1.810 inches and 1.870 inches First End Taper Length: 0.030 inches **Second End Taper Length:** 0.340 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.3125 inches **Second Shank Diameter:** Between 0.374 inches and 0.376 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees **Second End Tip Radius:** 0.120 inches **Second End Taper Angle:** 30.0 degrees **Second Shank Length:**

Material:

Steel comp xm-12

Between 1.018 inches and 1.038 inches

NSN 5315-01-485-6753

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Ams 5659 assn standard single material response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0