NSN 5315-01-485-7314

Headed Shoulder Pin - Page 1 of 2



G
View Online at https://aerobasegroup.com/nsn/5315-01-485-7314
First End Style:
Chamfered
Head Style:
Double chamfer
Under Head Length:
4.450 inches
First Step Diameter:
1.500 inches
First Step Length:
3.455 inches
Second Step Diameter:
0.750 inches
Second Step Length:
0.995 inches
Hole Arrangement Style:
Both end drilled
First Hole Diameter:
0.500 inches
Second Hole Diameter:
0.500 inches
Distance From Centerline Of Hole To End Of Pin:
1.380 inches
Center To Center Distance Between Holes:
1.325 inches
End Application:
Dashpot, 2.746/2.748 diameter sub-assembly hydraulic cylinder
First End Taper Length:
Between 0.040 inches and 0.060 inches
First End Taper Angle:
45.0 degrees
Pin Head Diameter:
2.000 inches
Special Features:
Head threaded 2-12unc-2a: first end threaded 3/4-10unc-3a

Height:

1.000 inches

Material:

Nickel alloy k-500 or nickel alloy 502

Material Specification:

Qq-n-286, class a or class b federal specification single material response

Style Designator:

Shoulder

NSN 5315-01-485-7314

Headed Shoulder Pin - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0