NSN 5315-01-486-5449

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-486-5449

| First | End Style: |
|---------|--|
| Charr | nfered |
| Head | l Style: |
| Flat c | shamfer |
| Width | h Between Flats: |
| 0.375 | 5 inches |
| Unde | er Head Length: |
| 1.063 | 3 inches |
| First | Step Diameter: |
| Betwe | een 0.998 inches and 0.999 inches |
| First | Step Length: |
|).500 |) inches |
| Seco | nd Step Diameter: |
|).875 | 5 inches |
| Seco | nd Step Length: |
| 0.563 | 3 inches |
| Interr | nal Drive Style: |
| Socke | et |
| End / | Application: |
| Missli | ie tube assembly; los angeles class ssn (688) |
| First | End Taper Length: |
| 0.062 | 2 inches |
| First | End Taper Angle: |
| 45.0 (| degrees |
| Pin H | lead Diameter: |
| Betwe | een 1.237 inches and 1.239 inches |
| Prod | uct Name: |
| Alignr | ment pin |
| Spec | ial Features: |
| First o | end threaded 7/8-14unf-2a x .562 lg; .281 in. From first end hole drilled .250 in. Diameter x .188219 in. Dp for nylon insert (p/n 16) |
| Heigł | ht: |
| 0.375 | 5 inches |
| Mate | rial: |
| Steel | comp 630 |
| Mate | rial Specification: |
| Astm | -a564 assn standard single material response |
| Style | Designator: |
| Shoul | lder |
| Shelf | Life: |
| N/a | |
| | Of Measure: |

NSN 5315-01-486-5449

Headed Shoulder Pin - Page 2 of 2

Demilitarization:

No

Fiig:

A212a0

