

View Online at <https://aerobasegroup.com/nsn/5315-01-490-1001>

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 3.100 inches and 3.120 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c

Shoulder To Head End Distance:

1.600 inches

Pin Center To Handle End Distance:

1.860 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Special Features:

Assembly contains 2-sleeve-ms51844-62 or ms51844-22; wire rope, type ii, cmpsn b, nylon jacket, specification mil-w-83420; retaining clip, 12308427-1; quick release pin, ms17986c831

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0