

View Online at <https://aerobasegroup.com/nsn/5315-01-490-1001>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 3.100 inches and 3.120 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c

**Shoulder To Head End Distance:**

1.600 inches

**Pin Center To Handle End Distance:**

1.860 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Special Features:**

Assembly contains 2-sleeve-ms51844-62 or ms51844-22; wire rope, type ii, cmprn b, nylon jacket, specification mil-w-83420; retaining clip, 12308427-1; quick release pin, ms17986c831

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0