

View Online at <https://aerobasegroup.com/nsn/5315-01-490-1290>

Head Diameter:

Between 0.640 inches and 0.755 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Lanyard Length:

Between 9.750 inches and 10.250 inches

Actuation Method:

Push button

End Application:

Test set electronic sys

Grip Length:

Between 1.100 inches and 1.120 inches

Actuation Type:

Push and pull

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

1.270 inches

Pin Center To Handle End Distance:

Between 1.530 inches and 1.655 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

0.590 inches

Product Name:

Lanyard pin assembly

Special Features:

Lanyard pin assembly contains: p/n 12354581-terminal; m83420/4-001-wire rope; 12354582-sleeve; ms17989-c811-pin

Material:

Steel comp 630 spindle or steel comp 631 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

L handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0