

View Online at <https://aerobasegroup.com/nsn/5315-01-490-1290>

**Head Diameter:**

Between 0.640 inches and 0.755 inches

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Detent Quantity:**

2

**Lanyard Length:**

Between 9.750 inches and 10.250 inches

**Actuation Method:**

Push button

**End Application:**

Test set electronic sys

**Grip Length:**

Between 1.100 inches and 1.120 inches

**Actuation Type:**

Push and pull

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

36800 double pound

**Shoulder To Head End Distance:**

1.270 inches

**Pin Center To Handle End Distance:**

Between 1.530 inches and 1.655 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

0.590 inches

**Product Name:**

Lanyard pin assembly

**Special Features:**

Lanyard pin assembly contains: p/n 12354581-terminal; m83420/4-001-wire rope; 12354582-sleeve; ms17989-c811-pin

**Material:**

Steel comp 630 spindle or steel comp 631 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

L handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0