NSN 5315-01-497-0644

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-497-0644 **Head Diameter:** Between 1.530 inches and 1.700 inches **Shoulder Diameter:** Between 0.810 inches and 0.975 inches **Shank Diameter:** Between 0.622 inches and 0.625 inches **Detent Quantity:** 2 **Actuation Method:** Push button **End Application:** Hoist **Grip Length:** 2.093 inches **Actuation Type:** Push **Shear Strength:** 51200 double pounds per square inch **Shoulder To Head End Distance:** Between 0.950 inches and 1.500 inches **Detent To Tapered End Distance:** Between 0.530 inches and 0.580 inches **Product Name:** Pin, ball-lok, quick release positive locking, single acting button handle Material: Steel comp 4130 spindle **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Cadmium spindle **Surface Treatment Specification:** Qq-p-416, type2, class2 federal specification 1st treatment response collar and qq-p-35 federal specification 2nd treatment response collar **Style Designator:** Ring handle Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

Fiig:

A212a0

NSN 5315-01-497-0644

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.