

View Online at <https://aerobasegroup.com/nsn/5315-01-499-9371>

**First End Style:**

Chamfered

**Overall Length:**

2.000 inches

**Diameter:**

Between 0.247 inches and 0.251 inches

**Effective Length:**

Between 1.212 inches and 1.215 inches

**Undercut Diameter:**

Between 0.208 inches and 0.212 inches

**Undercut Width:**

Between 0.029 inches and 0.032 inches

**Undercut Radius:**

0.005 inches

**End Application:**

Armored panel; helicopter, search and rescue, hh-60h

**First End Taper Length:**

0.040 inches

**Second End Relationship With First End:**

Identical

**First End Location:**

Long end

**First End Taper Angle:**

45.0 degrees

**Product Name:**

Locking pin

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate and oxide

**Surface Treatment Specification:**

Qq-p-35, ty ii or viii federal specification 1st treatment response and mil-c-13924, cl 3 military specification 2nd treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-c-13924 spec.