

View Online at <https://aerobasegroup.com/nsn/5315-01-501-3452>

First End Style:

Slotted

Second End Style:

Chamfered

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.570 inches

Shoulder Diameter:

1.000 inches

Overall Length:

2.380 inches

First Step Diameter:

0.750 inches

Second Step Diameter:

0.750 inches

Second Step Length:

1.090 inches

Third Step Diameter:

0.650 inches

Third Step Length:

0.660 inches

End Application:

Universal puller kit`

Shoulder Length:

0.060 inches

First End Slot Width:

0.070 inches

First End Slot Depth:

0.120 inches

Second End Taper Length:

Between 0.080 inches and 0.090 inches

Thready Qty Per Inch (tpi):

16

Second End Relationship With First End:

Not identical

Hardness Rating:

40.0 rockwell c and 45.0 rockwell c

Thread Size:

0.750 inches

First End Location:

Slot end

Second End Taper Angle:

Between 44.5 degrees and 45.5 degrees

Product Name:

Pin, threaded

Material:

Steel comp 8640 or steel comp 4140

Material Specification:

Astm a322 assn standard all material responses or astm a331 assn standard all material responses

Style Designator:

Shoulder

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0