

View Online at <https://aerobasegroup.com/nsn/5315-01-501-3452>

**First End Style:**

Slotted

**Second End Style:**

Chamfered

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.570 inches

**Shoulder Diameter:**

1.000 inches

**Overall Length:**

2.380 inches

**First Step Diameter:**

0.750 inches

**Second Step Diameter:**

0.750 inches

**Second Step Length:**

1.090 inches

**Third Step Diameter:**

0.650 inches

**Third Step Length:**

0.660 inches

**End Application:**

Universal puller kit`

**Shoulder Length:**

0.060 inches

**First End Slot Width:**

0.070 inches

**First End Slot Depth:**

0.120 inches

**Second End Taper Length:**

Between 0.080 inches and 0.090 inches

**Thready Qty Per Inch (tpi):**

16

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

40.0 rockwell c and 45.0 rockwell c

**Thread Size:**

0.750 inches

**First End Location:**

Slot end

**Second End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Product Name:**

Pin, threaded

**Material:**

Steel comp 8640 or steel comp 4140

**Material Specification:**

Astm a322 assn standard all material responses or astm a331 assn standard all material responses

**Style Designator:**

Shoulder

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0