NSN 5315-01-501-7862

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-501-7862
First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.655 inches
Shoulder Width Across Flats:
Between 0.430 inches and 0.439 inches
Shank Diameter:
0.189 inches
Overall Length:
Between 1.105 inches and 1.125 inches
End Application:
Arr list code; f/a-18e forward fuselage misc
Second End Taper Length:
0.200 inches
Thready Qty Per Inch (tpi):
32
Second End Relationship With First End:
Not identical
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.219 inches and 0.220 inches
First End Location:
Threaded end
Second End Tip Radius:
Between 0.060 inches and 0.090 inches
Second Shank Length:
0.450 inches
Material:
Steel comp 302 or steel comp 304 or steel comp 303se
Material Specification:
Qq-s-763 cond b federal specification 1st material response or qq-s-763 cond b federal specification 2nd material response or mms265
cond b fscm 76301 mfr ref 3rd material response
Surface Treatment:

Passivate

NSN 5315-01-501-7862

Headless Shoulder Pin - Page 2 of 2



Surface Treatment Specification:	
Ams qq-p-35 assn standard single treatment response	
Style Designator:	
Shoulder	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

No

Demilitarization:

Fiig:

A212a0