NSN 5315-01-502-5679



Knurled Straight Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-01-502-5679 First End Style: Chamfered w/thru hole **Second End Style:** Chamfered w/thru hole **Overall Length:** 2.250 inches Diameter: Between 0.4980 inches and 0.4985 inches **End Application:** Plate, tooling support; f16 engine First End Taper Length: 0.160 inches Second End Taper Length: 0.060 inches **Knurl Outside Diameter:** 0.750 inches **Knurl Length:** 1.000 inches Second End Relationship With First End: Not identical **Hardness Rating:** 55.0 rockwell c and 59.0 rockwell c First End Taper Angle: 30.0 degrees **Second End Taper Angle:** 45.0 degrees **Special Features:** Knurled head flat edge 0.600 in. Dia. Steel

Material:	

Material Specification:

Sae 01 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Style Designator:

Diamond knurled

Shelf Life:

N/a

Unit Of Measure:

NSN 5315-01-502-5679

Knurled Straight Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-c-13924 spec.