

View Online at <https://aerobasegroup.com/nsn/5315-01-502-6264>

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Button Handle Diameter:

Between 1.300 inches and 1.400 inches

Detent Quantity:

4

Lanyard Length:

Between 11.500 inches and 12.500 inches

Actuation Method:

Push button

End Application:

Seawolf class ssn

Grip Length:

Between 4.300 inches and 4.320 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

36800 double pound

Shoulder To Head End Distance:

Between 1.140 inches and 1.580 inches

Pin Attachment Type:

Cable lanyard w/terminations

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Special Features:

Lanyard is attached to tab with mounting hole diameter 0.194 in.

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0