

View Online at <https://aerobasegroup.com/nsn/5315-01-502-6264>

**Shank Diameter:**

Between 0.4970 inches and 0.4985 inches

**Button Handle Diameter:**

Between 1.300 inches and 1.400 inches

**Detent Quantity:**

4

**Lanyard Length:**

Between 11.500 inches and 12.500 inches

**Actuation Method:**

Push button

**End Application:**

Seawolf class ssn

**Grip Length:**

Between 4.300 inches and 4.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

36800 double pound

**Shoulder To Head End Distance:**

Between 1.140 inches and 1.580 inches

**Pin Attachment Type:**

Cable lanyard w/terminations

**Detent To Tapered End Distance:**

Between 0.430 inches and 0.460 inches

**Special Features:**

Lanyard is attached to tab with mounting hole diameter 0.194 in.

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0