NSN 5315-01-505-5867

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-505-5867 **Head Diameter:** Between 0.500 inches and 0.505 inches **Shank Diameter:** Between 0.497 inches and 0.498 inches **Detent Quantity: Actuation Method:** Handle **End Application:** Consolidated ground support equipment **Grip Length:** 2.800 inches **Actuation Type:** Pull and push **Shear Strength:** 36800 double pounds per square inch **Shoulder To Head End Distance:** 1.270 inches Pin Center To Handle End Distance: Between 1.530 inches and 1.655 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** 0.590 inches **Special Features:** Pin, quick release, self-retaining, positive locking, double acting, I handle Material: Steel comp 630 spindle **Material Specification:** Qq-s-766 federal specification 1st material response ring **Surface Treatment:** Passivate ring **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response ring **Style Designator:** L handle Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5315-01-505-5867

Quick Release Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.