## NSN 5315-01-514-6674

Headless Shoulder Pin - Page 1 of 2

First End Style: Chamfered



View Online at https://aerobasegroup.com/nsn/5315-01-514-6674

Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.4050 inches
Shank Length:
0.7175 inches
Shoulder Diameter:
0.4380 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Overall Length:
1.4050 inches
Second End Taper Length:
Between 0.2480 inches and 0.2520 inches
Thready Qty Per Inch (tpi):
28
Second End Relationship With First End:
Not identical
Thread Size:
0.2500 inches
Second Shank Diameter:
Between 0.3120 inches and 0.3125 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second End Tip Radius:
Between 0.0600 inches and 0.0900 inches
Second End Taper Angle:
45.0 degrees
Second Shank Length:
0.5620 inches
Material:
Titanium alloy uns r56400
Material Specification:
Mil-t-9047, type 3, cond a military specification single material response

## NSN 5315-01-514-6674

Headless Shoulder Pin - Page 2 of 2



Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Mil-t-9047 spec.