## NSN 5315-01-516-4059

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-516-4059

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Shank Length:
Between 0.505 inches and 0.545 inches
Shoulder Width Across Flats:
0.500 inches
Shank Diameter:
Between 0.3145 inches and 0.3155 inches
Overall Length:
1.140 inches
End Application:
B2 satcom kit
First End Taper Length:
0.046 inches
Thready Qty Per Inch (tpi):
28 Second End Balationship With First End:
Second End Relationship With First End: Not identical
Thread Size:
0.250 inches
Second Shank Diameter:
0.315 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second End Tip Radius:
0.060 inches
Second End Taper Angle:
Between 25.0 degrees and 35.0 degrees
Second Shank Length:
Between 0.480 inches and 0.500 inches
Product Name:
Pin, rear mounting
Material:
Steel comp 302 and steel comp 304

## NSN 5315-01-516-4059

Headless Shoulder Pin - Page 2 of 2



Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Style Designator: Shoulder **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A212a0