NSN 5315-01-518-5800

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-518-5800 First End Style: Chamfered Second End Style: Chamfered **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Shank Length:** 0.470 inches **Shoulder Diameter:** Between 0.367 inches and 0.376 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Overall Length:** 1.035 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.076 inches and 0.086 inches Distance From Centerline Of Hole To End Of Pin: 0.140 inches **End Application:** Aircraft, hornet f/a-18 (e/f) First End Taper Length: 0.030 inches Second End Taper Length: Between 0.170 inches and 0.210 inches Thready Qty Per Inch (tpi): Second End Relationship With First End: Not identical **Thread Size:** 0.1900 inches **Second Shank Diameter:** Between 0.1851 inches and 0.1863 inches **First End Location:**

Threaded end

First End Taper Angle:

45.0 degrees

NSN 5315-01-518-5800

Headless Shoulder Pin - Page 2 of 2



| Second End Tip Radius: |
|---|
| Between 0.060 inches and 0.090 inches |
| Second Shank Length: |
| 0.440 inches |
| Material: |
| Steel |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A242a0 |