

View Online at <https://aerobasegroup.com/nsn/5315-01-520-7454>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Pinlength:**

4.157 inches

**Pindiameter:**

Between 1.3390 inches and 1.3998 inches

**End Application:**

Nha 4j40101, used on ma0001a

**First End Taper Length:**

0.040 inches

**Second End Taper Length:**

0.070 inches

**Second End Relationship With First End:**

Not identical

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.0 microinches outside diameter

**Second End Taper Angle:**

45.0 degrees

**Product Name:**

Pin-flap attachment, upper

**Special Features:**

1st end internal threads 0.338/.331 dia-.59 deep, csk 100 degrees x .41 dia, 3/8 - 24 unf-3b .38 deep; second end 1.400 length, 0.749 in min and 0.758 in maximum dia; through slot hole 0.300 wide, 0.191 in to 0.198 in maximum height, 1.330 in from second end; finish g-53, internal threads and holes should be coated with zinc phosphate by immersion per stp 58-302, type 1, cl 2 and overcoat solid film lubricant applied per stp 62-005, type iv, sides and ends of pin coated with karon-type b or equivalent (kamatics corp, bloomfield, ct

**Material:**

Steel

**Material Specification:**

Ams 6532 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0