

View Online at <https://aerobasegroup.com/nsn/5315-01-521-3490>

First End Style:

Chamfered

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.750 inches

Shank Length:

0.020 inches

Shoulder Width Across Flats:

0.369 inches

Shank Diameter:

0.279 inches

Overall Length:

1.830 inches

Undercut Diameter:

0.190 inches

Undercut Width:

0.050 inches

End Application:

B1b, 92e9110000

First End Taper Length:

0.020 inches

Thready Qty Per Inch (tpi):

28

Second End Relationship With First End:

Identical

Thread Size:

0.250 inches

Second Shank Diameter:

0.210 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Surface Finish:

125.0 microinches

Second Shank Length:

0.822 inches

Product Name:

Pin, shock

Special Features:

Unthreaded portion has a cutaway/smaller diameter 0.310 in. Long 0.130 in. From shoulder to a diameter of 0.180

Material:

Steel comp 304

Material Specification:

Astm a276 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a967 assn standard single treatment response

Style Designator:

Undercut

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0