NSN 5315-01-525-1916

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-525-1916

First End Style:
Square
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.405 inches
Shank Length:
0.620 inches
Shoulder Width Across Flats:
Between 0.430 inches and 0.439 inches
Shank Diameter:
Between 0.249 inches and 0.250 inches
Overall Length:
1.400 inches
First End Taper Length:
Between 0.100 inches and 0.140 inches
Second End Taper Length:
0.030 inches
Thready Qty Per Inch (tpi):
rineady with er inch (tpi).
28
28
28 Second End Relationship With First End:
28 Second End Relationship With First End: Not identical
28 Second End Relationship With First End: Not identical Thread Size:
28 Second End Relationship With First End: Not identical Thread Size: 0.250 inches
28 Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter:
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location:
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius:
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches Second End Tip Radius:
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches Second End Tip Radius: Between 0.060 inches and 0.090 inches
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches Second End Tip Radius: Between 0.060 inches and 0.090 inches Second End Taper Angle:
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches Second End Tip Radius: Between 0.060 inches and 0.090 inches Second End Taper Angle: 45.0 degrees
Second End Relationship With First End: Not identical Thread Size: 0.250 inches Second Shank Diameter: Between 0.249 inches and 0.250 inches First End Location: Unthreaded end First End Tip Radius: Between 0.060 inches and 0.090 inches Second End Tip Radius: Between 4.060 inches and 0.090 inches Second End Taper Angle: 45.0 degrees Second Shank Length:

NSN 5315-01-525-1916

Headless Shoulder Pin - Page 2 of 2



Material Specification:
Sae-ams-5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Sae-ams-qq-p-35 assn standard single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0