

View Online at <https://aerobasegroup.com/nsn/5315-01-525-7350>

Shank Diameter:

Between 0.497 inches and 0.499 inches

Button Handle Diameter:

0.950 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.400 inches and 2.420 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

32800 double pound

Shoulder To Head End Distance:

1.820 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.530 inches

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

Astma484 assn standard all material responses collar or astm a581/582 assn standard all material responses collar or astm a240 assn standard all material responses collar or ams5513 assn standard all material responses collar or as-5516 assn standard all material responses collar or ams5640 assn standard all material responses collar

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response head

Style Designator:

Button

Specification Data:

80205-nas1338 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.