

View Online at <https://aerobasegroup.com/nsn/5315-01-525-7350>

**Shank Diameter:**

Between 0.497 inches and 0.499 inches

**Button Handle Diameter:**

0.950 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 2.400 inches and 2.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

32800 double pound

**Shoulder To Head End Distance:**

1.820 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.530 inches

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

Astma484 assn standard all material responses collar or astm a581/582 assn standard all material responses collar or astm a240 assn standard all material responses collar or ams5513 assn standard all material responses collar or as-5516 assn standard all material responses collar or ams5640 assn standard all material responses collar

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response head

**Style Designator:**

Button

**Specification Data:**

80205-nas1338 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.