

View Online at <https://aerobasegroup.com/nsn/5315-01-525-7351>

Head Diameter:

Between 0.390 inches and 0.505 inches

Shank Diameter:

Between 0.310 inches and 0.311 inches

Detent Quantity:

2

Grip Length:

Between 0.190 inches and 0.210 inches

Actuation Type:

Pull and push

Features Provided:

Drive out feature

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

2800 double pound

Shoulder To Head End Distance:

1.730 inches

Pin Center To Handle End Distance:

1.750 inches

Pin Attachment Type:

Hook

Detent To Tapered End Distance:

0.440 inches

Material:

Steel comp 631 spring or steel comp 302 spring

Material Specification:

Mil-s-6758 military specification 1st material response handle and ams-qq-763 assn standard 2nd material response handle and astm a484/582 assn standard 3rd material response handle or ams5640 assn standard 3rd material response handle

Surface Treatment:

Passivate ring

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response button and ams-qq-p-416 type 2 class 2 assn standard 2nd treatment response button

Style Designator:

L handle

Specification Data:

80205-nas1353 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.