

View Online at <https://aerobasegroup.com/nsn/5315-01-526-3542>

**First End Style:**

Square

**Head Style:**

Flat

**Diameter:**

0.438 inches

**Effective Length:**

1.148 inches

**Undercut Diameter:**

0.412 inches

**Under Head Length:**

1.128 inches

**Undercut Radius:**

0.005 inches

**Hole Arrangement Style:**

Drilled through center

**First Hole Diameter:**

0.063 inches

**End Application:**

B-52

**Grip Length:**

1.120 inches

**Pin Head Diameter:**

0.380 inches

**Product Name:**

Pin, uplock link tip protection gear

**Special Features:**

Head tap drill .20 deep thd 1/4 in. -28unf-2b per mil-s-7742 .13 min depth of complete thd. Csk 110 degree to maj diameter of thd; silver plated, diameter before plating 0.4380 after plating 0.4400; head has a flat side; another hole sideways to first hole 0.560 from bottom of head, 0.065 in dia

**Height:**

0.130 inches

**Material:**

Steel comp 8630 or steel comp 4130

**Material Specification:**

Mil-s-6050 military specification single material response or mil-s-6758 military specification single material response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6050 spec.