

View Online at <https://aerobasegroup.com/nsn/5315-01-526-3542>

First End Style:

Square

Head Style:

Flat

Diameter:

0.438 inches

Effective Length:

1.148 inches

Undercut Diameter:

0.412 inches

Under Head Length:

1.128 inches

Undercut Radius:

0.005 inches

Hole Arrangement Style:

Drilled through center

First Hole Diameter:

0.063 inches

End Application:

B-52

Grip Length:

1.120 inches

Pin Head Diameter:

0.380 inches

Product Name:

Pin, uplock link tip protection gear

Special Features:

Head tap drill .20 deep thd 1/4 in. -28unf-2b per mil-s-7742 .13 min depth of complete thd. Csk 110 degree to maj diameter of thd; silver plated, diameter before plating 0.4380 after plating 0.4400; head has a flat side; another hole sideways to first hole 0.560 from bottom of head, 0.065 in dia

Height:

0.130 inches

Material:

Steel comp 8630 or steel comp 4130

Material Specification:

Mil-s-6050 military specification single material response or mil-s-6758 military specification single material response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A212a0

Mil-std (military Standard):

Mil-s-6050 spec.