NSN 5315-01-532-3276

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-532-3276

| First End Style: Square Shank Length: 0.438 inches Shoulder Diameter: 0.500 inches Shank Diameter: 0.749 inches Undercut Diameter: 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
|--|---------------------------------------|
| Shank Length:0.438 inchesShoulder Diameter:0.500 inchesShank Diameter:0.749 inchesUndercut Diameter:0.408 inchesUndercut Width:0.082 inchesEnd Application:F100-pw-200 (f16a/b/c/d) aircraft engine, fixturSecond End Relationship With First End:Not identicalFirst End Location:Shank endProduct Name: | re, lift and rotate-intermediate case |
| 0.438 inches Shoulder Diameter: 0.500 inches Shank Diameter: 0.749 inches Undercut Diameter: 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Shoulder Diameter:0.500 inchesShank Diameter:0.749 inchesUndercut Diameter:0.408 inchesUndercut Width:0.082 inchesEnd Application:F100-pw-200 (f16a/b/c/d) aircraft engine, fixturSecond End Relationship With First End:Not identicalFirst End Location:Shank endProduct Name: | re, lift and rotate-intermediate case |
| 0.500 inches Shank Diameter: 0.749 inches Undercut Diameter: 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Shank Diameter:0.749 inchesUndercut Diameter:0.408 inchesUndercut Width:0.082 inchesEnd Application:F100-pw-200 (f16a/b/c/d) aircraft engine, fixturSecond End Relationship With First End:Not identicalFirst End Location:Shank endProduct Name: | re, lift and rotate-intermediate case |
| 0.749 inches Undercut Diameter: 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Undercut Diameter: 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| 0.408 inches Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Undercut Width: 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| 0.082 inches End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| End Application: F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| F100-pw-200 (f16a/b/c/d) aircraft engine, fixtur Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Second End Relationship With First End: Not identical First End Location: Shank end Product Name: | re, lift and rotate-intermediate case |
| Not identical First End Location: Shank end Product Name: | |
| First End Location: Shank end Product Name: | |
| Shank end Product Name: | |
| Product Name: | |
| | |
| _ | |
| Dowel pin | |
| Special Features: | |
| Shoulder end appears to be threaded | |
| Material: | |
| Steel comp 1018 | |
| Material Specification: | |
| Aisi 1018 assn standard single material respon | ISE |
| Style Designator: | |
| Undercut | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A212a0 | |