NSN 5315-01-536-1337

Headless Shoulder Pin - Page 1 of 2

First End Style: Chamfered Thread Class:



View Online at https://aerobasegroup.com/nsn/5315-01-536-1337

3a
Thread Direction:
Right-hand
Thread Length:
0.140 inches
Shank Length:
0.140 inches
Shoulder Diameter:
Between 0.395 inches and 0.405 inches
Shank Diameter:
Between 0.134 inches and 0.144 inches
Overall Length:
1.030 inches
Undercut Diameter:
Between 0.134 inches and 0.144 inches
Undercut Width:
0.070 inches
End Application:
C-17a
First End Taper Length:
0.020 inches
Second End Relationship With First End:
Identical
Hardness Rating:
57.0 rockwell c and 60.0 rockwell c
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.188 inches and 0.190 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second Shank Length:
0.330 inches
Product Name:
Pin, detent
Special Features:
Shoulder is oval 0.275 in min and 0.285 in maximum width and is offset 0.135in min and 0.145 in maximum from one side

NSN 5315-01-536-1337

Headless Shoulder Pin - Page 2 of 2



Material:
Steel comp 440c
Style Designator:
Undercut
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A212a0