## NSN 5315-01-536-1337

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-01-536-1337

First End Style-
First End Style: Chamfered
Thread Class:
3a
Thread Direction:
Right-hand Thread Length:
0.140 inches
Shank Length: 0.140 inches
Shoulder Diameter:
Between 0.395 inches and 0.405 inches
Shank Diameter:
Between 0.134 inches and 0.144 inches
Overall Length:
1.030 inches
Undercut Diameter:
Between 0.134 inches and 0.144 inches
Undercut Width:
0.070 inches
End Application:
C-17a
First End Taper Length:
0.020 inches
Second End Relationship With First End:
Identical
Hardness Rating:
57.0 rockwell c and 60.0 rockwell c
Thread Size:
0.190 inches
Second Shank Diameter:
Between 0.188 inches and 0.190 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Second Shank Length:
0.330 inches
Product Name:
Pin, detent
Special Features:

Shoulder is oval 0.275 in min and 0.285 in maximum width and is offset 0.135in min and 0.145 in maximum from one side

## NSN 5315-01-536-1337

Headless Shoulder Pin - Page 2 of 2

Material:

Steel comp 440c

Style Designator:

Undercut

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

