

View Online at <https://aerobasegroup.com/nsn/5315-01-567-9803>

**First End Style:**

Chamfered

**Head Style:**

Flat fillister

**Width Between Flats:**

Between 8.0 millimeters and 8.1 millimeters

**Under Head Length:**

Between 16.7 millimeters and 17.2 millimeters

**First Step Diameter:**

Between 13.1 millimeters and 13.4 millimeters

**First Step Length:**

10.5 millimeters

**Second Step Diameter:**

Between 12.6 millimeters and 12.7 millimeters

**Second Step Length:**

Between 6.3 millimeters and 6.8 millimeters

**Internal Drive Style:**

Socket

**End Application:**

End item nsn: 1340-01-517-4757; mlrs multiple launch rocket system

**First End Taper Length:**

Between 0.5 millimeters and 0.8 millimeters

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

Between 16.8 millimeters and 17.0 millimeters

**Surface Finish:**

3.2 micrometers

**Product Name:**

Pin, shoulder, threaded

**Special Features:**

First shoulder under head is metric threaded, m13.4x1.5

**Height:**

Between 10.0 millimeters and 10.5 millimeters

**Material:**

Steel comp 1020 or steel comp 1021 or steel comp 1022

**Material Specification:**

A576. Cond a assn standard all material responses

**Surface Treatment:**

Cadmium and wax

**Surface Treatment Specification:**

Qq-p-416, type 2. Cl 2 federal specification 1st treatment response and mil-w-3688 military specification 2nd treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-w-3688 spec.