

View Online at <https://aerobasegroup.com/nsn/5315-01-567-9803>

First End Style:

Chamfered

Head Style:

Flat fillister

Width Between Flats:

Between 8.0 millimeters and 8.1 millimeters

Under Head Length:

Between 16.7 millimeters and 17.2 millimeters

First Step Diameter:

Between 13.1 millimeters and 13.4 millimeters

First Step Length:

10.5 millimeters

Second Step Diameter:

Between 12.6 millimeters and 12.7 millimeters

Second Step Length:

Between 6.3 millimeters and 6.8 millimeters

Internal Drive Style:

Socket

End Application:

End item nsn: 1340-01-517-4757; mlrs multiple launch rocket system

First End Taper Length:

Between 0.5 millimeters and 0.8 millimeters

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

Between 16.8 millimeters and 17.0 millimeters

Surface Finish:

3.2 micrometers

Product Name:

Pin, shoulder, threaded

Special Features:

First shoulder under head is metric threaded, m13.4x1.5

Height:

Between 10.0 millimeters and 10.5 millimeters

Material:

Steel comp 1020 or steel comp 1021 or steel comp 1022

Material Specification:

A576. Cond a assn standard all material responses

Surface Treatment:

Cadmium and wax

Surface Treatment Specification:

Qq-p-416, type 2. Cl 2 federal specification 1st treatment response and mil-w-3688 military specification 2nd treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A212a0

Mil-std (military Standard):

Mil-w-3688 spec.