NSN 5315-01-572-0917

Threaded Straight Pin - Page 1 of 2

Steel comp 303se



View Online at https://aerobasegroup.com/nsn/5315-01-572-0917

First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.290 inches
Pinlength:
Between 1.555 inches and 1.565 inches
Pindiameter:
Between 0.1200 inches and 0.1300 inches
End Application:
3020-01-542-9287
First End Taper Length:
0.010 inches
Second End Taper Length:
0.015 inches
Thready Qty Per Inch (tpi):
40
Second End Relationship With First End:
Not identical
Thread Size:
0.112 inches
First End Location:
Threaded end
First End Taper Angle:
45.0 degrees
Pin Grip Length:
Between 1.265 inches and 1.275 inches
Surface Finish:
32.0 microinches long shank
Second End Taper Angle:
45.0 degrees
Product Name:
Shaft, miter out
Special Features:
2nd end has 0.1865/0.1870 inch diameter head w/provision for dowel pin; at mid-length there is a collar; refer to drawing for additional
2nd end has 0.1865/0.1870 inch diameter head w/provision for dowel pin; at mid-length there is a collar; refer to drawing for additional details Material:

NSN 5315-01-572-0917

Threaded Straight Pin - Page 2 of 2



Material Specification:

Ams 5738 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a967, nitric 1 assn standard single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A212a0