

View Online at <https://aerobasegroup.com/nsn/5315-01-582-2836>

Shank Diameter:

0.188 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 0.400 inches and 0.420 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shear Strength:

5150 double pound

Shoulder To Head End Distance:

0.830 inches

Pin Attachment Type:

Ring

Detent To Tapered End Distance:

0.260 inches

Product Name:

Ball lok quick release pin

Special Features:

Standard b handle pin; single acting; pin meeets or exceed the requirements of mil-p-2346 (wep) and are available under nas 1333 through nas1346; when ordered under nas number a ring or hook must be attached to handle

Material:

Stainless steel spindle

Material Specification:

Astm a581/582 or ams-qq-a-225/6 or ams-qq-a-225/5; cres 303 or alum alloy 2024/2017 national std/spec all material responses button

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 assn standard all treatment responses

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0