

View Online at <https://aerobasegroup.com/nsn/5315-01-582-2836>

**Shank Diameter:**

0.188 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**Grip Length:**

Between 0.400 inches and 0.420 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shear Strength:**

5150 double pound

**Shoulder To Head End Distance:**

0.830 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.260 inches

**Product Name:**

Ball lok quick release pin

**Special Features:**

Standard b handle pin; single acting; pin meeets or exceed the requirements of mil-p-2346 (wep) and are available under nas 1333 through nas1346; when ordered under nas number a ring or hook must be attached to handle

**Material:**

Stainless steel spindle

**Material Specification:**

Astm a581/582 or ams-qq-a-225/6 or ams-qq-a-225/5; cres 303 or alum alloy 2024/2017 national std/spec all material responses button

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 assn standard all treatment responses

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0