# NSN 5315-01-585-8094

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-01-585-8094

## Handle Length:

2.350 inches

Shank Diameter:

Between 0.497 inches and 0.498 inches

# Detent Quantity:

1

### End Application:

Nsn 2355-01-529-2246 mine resistant vehicle

#### Grip Length:

0.630 inches

Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c shank

### Shear Strength:

38 double pound

#### Shoulder To Head End Distance:

1.660 inches

## **Detent To Tapered End Distance:**

0.460 inches

## **Product Name:**

Aluminum quick release pin

#### **Special Features:**

Stainless steel type - hardened stainless steel, quick release pin type - t-handle push-button, usable length 1.500 in, usable length tolerance +.020 in, hole size .500 in, handle - black aluminum with an anodized aluminum button, ball - two locking stainless steel balls, rockwell hardness c58 for the balls, installation instructions - just push the button to insert or remove the pin, note - split ring included, rockwell hardness including spindle with shank, diameter .500

Material:

Steel

# Style Designator:

T handle

# Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A212a0