

View Online at <https://aerobasegroup.com/nsn/5315-01-593-8943>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Internal Drive Style:**

Slot

**Pinlength:**

1.320 inches

**Pindiameter:**

Between 0.2350 inches and 0.2400 inches

**End Application:**

Interlock assembly lh; and interlock assembly lh tt (jb)

**Second End Slot Width:**

Between 0.041 inches and 0.049 inches

**First End Taper Length:**

0.030 inches

**Second End Slot Depth:**

Between 0.058 inches and 0.068 inches

**Thready Qty Per Inch (tpi):**

24

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.190 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Pin Grip Length:**

0.620 inches

**Product Name:**

Interlock cam key lock pin

**Special Features:**

Coat threads and seating face of fastener with molykote p-35 anti-galling compound eb p/n p37 prior to assembly

**Material:**

Nickel alloy and aluminum

**Material Specification:**

Astm a494 assn standard single material response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0