

View Online at <https://aerobasegroup.com/nsn/5315-01-593-8943>

First End Style:

Chamfered

Second End Style:

Slotted

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Internal Drive Style:

Slot

Pinlength:

1.320 inches

Pindiameter:

Between 0.2350 inches and 0.2400 inches

End Application:

Interlock assembly lh; and interlock assembly lh tt (jb)

Second End Slot Width:

Between 0.041 inches and 0.049 inches

First End Taper Length:

0.030 inches

Second End Slot Depth:

Between 0.058 inches and 0.068 inches

Thready Qty Per Inch (tpi):

24

Second End Relationship With First End:

Not identical

Thread Size:

0.190 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Pin Grip Length:

0.620 inches

Product Name:

Interlock cam key lock pin

Special Features:

Coat threads and seating face of fastener with molykote p-35 anti-galling compound eb p/n p37 prior to assembly

Material:

Nickel alloy and aluminum

Material Specification:

Astm a494 assn standard single material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0